

Dualys³

Technical data & specifications

Target markets:

- Identification
- Biometric security
- Education
- Transit
- ePayment
- Leisure



From bulk personalization of cards to individual card printing, Dualys³ is the one-stop color printer for dual-sided personalization of badges, sterling quality and robust security.

Thanks to the most advanced printing engine in the market, **Dualys³** prints high-definition badges within seconds.

This solution benefits from the latest encoding technologies: ISO or JIS2 magnetic tracks, and smart card with contact or contactless (RFID). These encoding options can be combined to personalize multifeatured cards in a single pass.

Dualys³ comes with a detachable 100-card feeder. Yet, you can also use it as a compact badge or card counter, thanks to a manual feed option that prints your badges one by one.

Because the Evolis products have earned market-proven reliability, Evolis is committed even further to superior quality and introduces a **3-year warranty** on the full **Dualys³** range of printers.

Standard Ship kit :

- Dualys³ printer
- Power supply
- Power cord
- USB cable
- eMedia Card designer
Incl. Excel database
- XP, 2003 and Vista drivers
- Cleaning starter kit
- 3-Year warranty
- RoHS compliant



This datasheet provides details regarding the above-mentioned item integrated into an Evolis printer. Please note that specifications and details are subject to change without notice and should therefore be confirmed by Evolis prior to any purchase.

evolis

Main Characteristics	<p>Dual-sided color printing module 300 dpi print head (11.8 dots/mm) USB port 16 MB RAM allowing two card storages (front & back) Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil) Output hopper with a capacity of 100 cards (0.76 mm - 30 mil) 1-Button and 4-LED control panel</p>															
Options & Accessories	<p>USB & Ethernet TCP-IP ports, internal USB Hub Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil) Manual card feeder for front-desk operation Dualys Travel Bag</p>															
Color	<p>Ocean Blue cover White housing</p>															
Encoding options <i>(Can be combined together)</i>	<p>Magnetic stripe encoder ISO 7811 HiCo/ LoCo or JIS2 Smart contact station - ISO 7816-2 Smart contact station and encoding unit - PC/SC, EMV 2000-1 Contactless encoding unit - ISO 14443A, B, ISO 15693, Mifare®, DesFire®, HID iCLASS®, HID PROX® <i>Other types upon request</i></p>															
Print mode	<p>Color dye sublimation and monochrome thermal transfer Enhanced color management system for top quality pictures Edge-to-edge printing Dual-sided printing Integrated ribbon saver for monochrome printing Integrated ½ Panel YMCKO picture management</p>															
Performance	<p>Color 1 side (YMCKO): 150 cards/hour Color 2 sides (YMCK0-K): 125 cards/hour Monochrome 1 side: up to 1000 cards/hour Monochrome 2 sides: up to 350 cards/hour</p>															
Ribbons	<p>2-panel KO black monochrome ribbon - 500 cards/roll 5-panel YMCKO color ribbon - 200 cards/roll 6-panel YMCKO-K color ribbon - 200 cards/roll Half-panel YMCKO color ribbon - 400 cards/roll Monochrome ribbons - up to 1000 cards/roll (black, red, green, blue, white, gold and silver) Varnish hologram - 350 cards/roll Scratch-Off - up to 1000 cards/roll</p>															
Supported platforms	<p>Windows™ XP, 2003 and Vista, 32 & 64 bits Mac™ OS X v10.2, 10.3 and 10.4 (free download) Linux (free download)</p>															
Software supplied	<p>eMedia Card Designer Software Standard Edition for designing and editing badges Connection to Microsoft™ Excel databases Data Import & Export feature Magnetic encoding Unlimited version</p>															
Cards characteristics	<table border="0"> <tr> <td>Types</td> <td colspan="2">All PVC, Composite PVC cards, PET, ABS1 and varnished1 cards</td> </tr> <tr> <td>Format</td> <td colspan="2">ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")</td> </tr> <tr> <td>Thickness</td> <td>From 0.25 mm (10 mil) to 1 mm (40 mil) - Dual-sided printing recommended</td> <td>from 0.50 mm (20 mil)</td> </tr> </table>	Types	All PVC, Composite PVC cards, PET, ABS1 and varnished1 cards		Format	ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")		Thickness	From 0.25 mm (10 mil) to 1 mm (40 mil) - Dual-sided printing recommended	from 0.50 mm (20 mil)						
Types	All PVC, Composite PVC cards, PET, ABS1 and varnished1 cards															
Format	ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")															
Thickness	From 0.25 mm (10 mil) to 1 mm (40 mil) - Dual-sided printing recommended	from 0.50 mm (20 mil)														
Warranty	<p>Printer, print head: 3-year warranty, unlimited number of passes, subject to observance of specific conditions and use of Evolis genuine consumables Use Evolis Genuine products for best performance and extended lifespan of your printer</p>															
Size & dimensions	<table border="0"> <tr> <td>Printer size</td> <td colspan="2">Height: 235 mm (9.25") - Length: 447 mm (17.59") - Width: 237 mm (9.33")</td> </tr> <tr> <td>Printer weight</td> <td colspan="2">7.4 Kg (16.31 Lbs)</td> </tr> </table>	Printer size	Height: 235 mm (9.25") - Length: 447 mm (17.59") - Width: 237 mm (9.33")		Printer weight	7.4 Kg (16.31 Lbs)										
Printer size	Height: 235 mm (9.25") - Length: 447 mm (17.59") - Width: 237 mm (9.33")															
Printer weight	7.4 Kg (16.31 Lbs)															
Electrical & Environmental	<table border="0"> <tr> <td>Electrical</td> <td colspan="2">Power supply: 110-230 Volts AC, 1.8 A, 60-50 Hertz - Printer: 24 Volts DC, 3 A</td> </tr> <tr> <td rowspan="4">Environmental</td> <td colspan="2">Min/max operating temperature: 15° / 30° C (59° / 86° F)</td> </tr> <tr> <td colspan="2">Humidity: 20% to 65% non-condensing</td> </tr> <tr> <td colspan="2">Min/max storage temperature: -5° / +70° C (23° / 158° F)</td> </tr> <tr> <td colspan="2">Storage humidity: 20% to 70% non-condensing</td> </tr> <tr> <td></td> <td colspan="2">Operating ventilation: free air</td> </tr> </table>	Electrical	Power supply: 110-230 Volts AC, 1.8 A, 60-50 Hertz - Printer: 24 Volts DC, 3 A		Environmental	Min/max operating temperature: 15° / 30° C (59° / 86° F)		Humidity: 20% to 65% non-condensing		Min/max storage temperature: -5° / +70° C (23° / 158° F)		Storage humidity: 20% to 70% non-condensing			Operating ventilation: free air	
Electrical	Power supply: 110-230 Volts AC, 1.8 A, 60-50 Hertz - Printer: 24 Volts DC, 3 A															
Environmental	Min/max operating temperature: 15° / 30° C (59° / 86° F)															
	Humidity: 20% to 65% non-condensing															
	Min/max storage temperature: -5° / +70° C (23° / 158° F)															
	Storage humidity: 20% to 70% non-condensing															
	Operating ventilation: free air															
Miscellaneous	<p>RoHS compliant</p>															

This datasheet provides details regarding the above-mentioned item integrated into an Evolis printer. Please note that specifications and details are subject to change without notice and should therefore be confirmed by Evolis prior to any purchase.